



## DigiSAT DSXO-1002C – GPON ONU

---



### TECHNICAL /FEATURES

---

#### 1. Overview

- DSXO-1002C is designed as HGU (Home Gateway Unit) in deferent FTTH solutions by DigiSAT, The carrier class FTTH application provides data service access.
- DSXO-1002C is based on mature and stable, cost-effective XPON technology. It can switch automatically with EPON and GPON when it access to the EPON OLT or GPON OLT.
- DSXO-1002C adopts high reliability, easy management, configuration flexibility and good quality of service (QoS) guarantees to meet the technical performance of the module of GPON Standard of ITU-TG.984.X

#### 2. Functional Feature

- Support EPON/GPON mode and switch mode automatically
- Support ONU auto-discovery/Link detection/remote upgrade of software
- WAN connections support Route and Bridge mode
- Route mode supports PPPoE/DHCP/ static IP
- Support QoS and DBA
- Support port Isolation and port vlan configuration
- Support Firewall function and IGMP snooping multicast feature
- Support LAN IP and DHCP Server configuration
- Support Port Forwarding and Loop-Detect
- Support TR069 remote configuration and maintenance
- Specialized design for system breakdown prevention to maintain stable system

## 3. Hardware Specification

Technical item	Details
PON Interface	1 G/EPON port(EPON PX 20 + and GPON Class B+) Receiving sensitivity: ≤-27dBm Transmitting optical power: 0~+4dBm Transmission distance: 20KM
Wavelength	TX: 1310nm, RX: 1490nm
Optical Interface	SC/APC Connector
LAN Interface	1 x 10/100/1000Mbps and 1 x 10/100Mbps auto adaptive Ethernet interfaces. Full/Half, RJ45 connector
CATV Interface	RF, WDM ,optical power : +2~-18dBm Optical reflection loss: ≥45dB Optical receiving wavelength: 1550±10nm RF frequency range: 47~1000MHz, RF output impedance: 75Ω RF output level: 78dBuV AGC range: 0~-15dBm MER: ≥32dB@-15dBm
LED	7 LED, For Status of PWR ` LOS ` PON ` LAN1~LAN2 ` Worn ` Normal
Push-Button	1,For Function of Reset
Operating Condition	Temperature: 0°C~+50°C Humidity: 10% ~ 90% (non-condensing)
Storing Condition	Temperature: -30°C~+60°C Humidity: 10%~90% (non-condensing)
Power Supply	DC 12V/1A
Power Consumption	≤6W
Dimension	155mm×92mm×34mm (L×W×H)
Net Weight	0.24Kg

## 4. Panel Lights Introduction

Pilot Lamp	Status	Description
PWR	On	The device is powered up.
	Off	The device is powered down.
LOS	Blink	The device does not receive optical signals.
	Off	The device has received optical signal.
PON	On	The device has registered to the PON system.
	Blink	The device is registering the PON system.
LAN1~LAN2	Off	The device registration is incorrect.
	On	Port (LANx) is connected properly (LINK).
	Blink	Port (LANx) is sending or/and receiving data (ACT).
Worn (CATV)	Off	Port (LANx) connection exception or not connected.
	On	Input optical power is higher than 3dbm or lower than -13dbm
Normal (CATV)	Off	Input optical power is between -13dbm and 3dbm
	On	Input optical power is higher than 3dbm or lower than -13dbm

## 5. Application

- Typical Solution : FTTO (Office) - FTTB (Building) - FTTH (Home)
- Typical Business : INTERNE IPTV, IP Camera, WiFi, Voip, CATV