



# DigiSAT DSXO-1004WV-AC – GPON ONU

---



## TECHNICAL /FEATURES

---

### 1. Overview

- DSXO-1004VW6 is AC1200 Dual Band as HGU (Home Gateway Unit) in deferent FTTH solutions by DigiSAT, The carrier class FTTH application provides data service access.
- DSXO-1004CVW6 is based on mature and stable, cost-effective XPON technology. It can switch automatically with EPON and GPON when it access to the EPON OLT or GPON OLT.
- DSXO-1004VW6 adopts high reliability, easy management, configuration flexibility and good quality of service (QoS) guarantees to meet the technical performance of the module of GPON Standard of ITU-TG.984.X

### 2. Functional Feature

- Support EPON/GPON mode and switch mode automatically
- Support ONU auto-discovery/Link detection/remote upgrade of software
- WAN connections support Route and Bridge mode
- Route mode supports PPPoE/DHCP/ static IP
- Support QoS and DBA
- Support port Isolation and port vlan configuration
- Support Firewall function and IGMP snooping multicast feature
- Support LAN IP and DHCP Server configuration
- Support Port Forwarding and Loop-Detect
- Support TR069 remote configuration and maintenance
- Specialized design for system breakdown prevention to maintain stable system

## Device Parameters

Operating temperature	0°C to 40°C	PON	XPON
Operating humidity	5% RH to 95% RH (non-condensing)	Port	4*GE+1*POTS+2.4G/5G WiFi 6 +1USB
Power consumption	12w	Optical connector	SC/UPC,SC/APC
PPPOE	Support	Warranty Time	12 months

## Software

Networking	QoS	Security	Management
<ul style="list-style-type: none"> <li>IPv4/IPv6 Dual Stack</li> <li>SNTP client</li> <li>NAT/ALG</li> <li>Static routing/Dynamic routing</li> <li>PPPoE client/passthrough</li> <li>DNS client/relay</li> <li>DHCP client/server</li> <li>IGMP and MLD snooping/proxy</li> </ul>	<ul style="list-style-type: none"> <li>Flexible packet classification</li> <li>Up to eight queues</li> <li>SP/WRR/SP+WRR</li> <li>Ingress rate limit</li> <li>Egress shaping</li> <li>WMM(Wi-Fi Multi Media)</li> </ul>	<ul style="list-style-type: none"> <li>Traffic filtering based on UNI port, VLAN ID, 802.1p, UNI+ 802.1p or VLAN+802.1p</li> <li>DoS attack defending</li> <li>Multiple VPN (IPSec, PPTP) passthrough</li> <li>MAC address filtering</li> <li>Broadcast/Unicast/Multicast attack protection</li> <li>Broadcast packet rate limit</li> <li>Dual image for firmware auto rollback</li> </ul>	<ul style="list-style-type: none"> <li>TR-069/OMCI remote management</li> <li>WEB GUI management</li> <li>Local built-in diagnostic function</li> <li>Logs and statistics</li> <li>Remote upgrade by HTTP</li> </ul>

## Others

Electrical Characteristics	Environmental Characteristics
<ul style="list-style-type: none"> <li>Power input: 12V DC</li> <li>Power consumption: 9W</li> </ul>	Operating temperature: 0 °C~ 40°C; (32°F ~ 104°F ) <ul style="list-style-type: none"> <li>Humidity: 5% ~ 95% (non-condensing)</li> </ul>